

Siemens Simatic Box PC 620 Model Selection

Basic Unit Includes:

AGP graphic on-board, 2 MB, 10/100 MB Ethernet RJ45, PC Card (PCMCIA type 3) watchdog, temperature safety functions, USB, 1 PCI, 1 ISA/PC1, 1 PC card

Model No. 6ES7647-2 - X 1

Processor/Interfaces

Pentium III 500 MHz, 256KB 2nd level cashe, MPI/PROFIBUS-DP 12 bit, w/o CLI

C

Pentium III 500 MHz, 256KB 2nd level cashe, w/o MPI/PROFIBUS-DP, w/o CLI

E

Celeron 500 MHz, 256KB 2nd level cashe, MPI/PROFIBUS-DP 12 bit, w/o CLI

F

Celeron 500 MHz, 256KB 2nd level cashe, w/o MPI/PROFIBUS-DP, w/o CLI

G

Drives

20 GB HHD EIDE, CD ROM 24x speed, ATAPI-SS

E

40 GB HHD EIDE, CD ROM 24x speed, ATAPI-SS

F

20 GB HHD EIDE

G

40 GB HHD EIDE

H

Memory

64 MB RAM

0

128 MB RAM

1

256 MB RAM

2

512 MB RAM

3

Expansions

Floppy Disk Drive 3.5", 1.44 MB

0

Super Disk LS 240

1

Power Supply

Europe (Euro connector)

0

USA (US Connector)

1

24 VDC Industrial Power Supply

2

UK Power Cable

3

CH Power Cable

4

Italian Power Cable

5

Operating System

MS-DOS 6.22

A

Windows NT 4.0 WS, English, SP 5

C

Windows NT 4.0 WS, German, SP 5

D

Windows 98 SE, English

G

Windows 98 SE, German

H

Windows 2000 Professional MUI (Gr, En, Fr, It, Sp)

J

Model No. 6ES7647-2 - X 1

Example: 6ES7647-2 C E 0 0 - 0 A X 1

Please let us know the exact model you require. It may be possible to customize a unit for your specific needs.



Classic Automation LLC
800 Salt Road
Webster, NY 14580
USA

www.classicautomation.com

Phone: +1 (585) 241-6010 FAX: +1 (585) 241-6014

email: sales@classicautomation.com