

Siemens Simatic Panel PC 670 Model Selection 6AV77

Model No. 6AV77		0	A	0
<b>Configuration</b>				
Central Configuration	2			
Distributed Configuration	3			
<b>Front Panels</b>				
10" TFT	1			
12" TFT Touch	2			
12" TFT	3			
15" TFT Touch	4			
15" TFT	5			
12" TFT Touch without front panel USB interface	6			
15" TFT Touch without front panel USB interface	7			
<b>RAM Configuration</b>				
128 MB RAM	1			
256 MB RAM	2			
512 MB RAM	3			
<b>Processors</b>				
Celeron 1.2 GHz	A			
Pentium III 1.26 GHz	B			
<b>Power Supply</b>				
PC and Operator Control Unit 24VDC	A			
PC and Operator Control Unit 110/230VAC US	B			
PC and Operator Control Unit 110/230VAC Europe	C			
PC 110/230VAC US and Operator Control Unit 24VDC	D			
PC 110/230VAC Europe and Operator Control Unit 24VDC	E			
PC 24VDC and Operator Control Unit 110/230VAC US	F			
PC 24VDC and Operator Control Unit 110/230VAC Europe	G			
<b>Drives</b>				
20 GB HD	0			
20 GB HD + CD-ROM	1			
40 GB HD	2			
40 GB HD + CD-ROM	3			
40 GB HD + CD-RW/DVD	4			
<b>Distance Between PC and Operator Control Unit (cable length)</b>				
0m (Central Configuration)	0			
2m	1			
5m	2			
10m	3			
20m	4			
<b>Operating System</b>				
No Operating System	A			
Windows NT 4.0 WS, German	B			
Windows NT 4.0 WS, English	C			
Windows 2000 Professional MUI (Gr, En, Fr, It, Sp)	D			
Windows 98, German	E			
Windows 98, English	F			
Windows XP Professional MUI (Gr, En, Fr, It, Sp)	G			

Please let us know the exact model you require. It may be possible to customize a unit for your specific needs.



Classic Automation LLC  
800 Salt Road  
Webster, NY 14580  
USA

[www.classicautomation.com](http://www.classicautomation.com)  
Phone: +1 (585) 241-6010 FAX: +1 (585) 241-6014  
email: sales@classicautomation.com